Before you start, check your Color Settings: for CMYK, select "U.S. Sheetfed Coated v2".

Open the Lavers Palette. Place your design on the **Design** laver.

Use the layer safe zone & instructions for reference only and delete it before submitting to Overnight Prints.

Keep all text and important image(s) within the safe zone to avoid being cut.

Extend your background all the way to the edge, beyond the trim mark for proper full bleed - if desired by the design.

To prepare your file for submitting to Overnight Prints:

Delete layer safe zone & instructions and

leave your Design layer and Art Board layer only. Do not delete the locked layer Art Board; this will ensure your file remains at the full bleed size when uploaded.

Save your file in .PDF, .EPS, .TIF, or .JPG format, in CMYK Color mode, with a resolution of 300 DPI.

Note: You may also submit your files in .AI (Illustrator version 8 or earlier), but our file uploader does not accept .AI files saved for versions later than Illustrator 8.

For more information on specs, orientation guide, common mistakes and postal regulations, visit:

http://www.overnightprints.com/main.php?A=specs

http://www.overnightprints.com/main.php?A=orientation

http://www.overnightprints.com/main.php?A=specs_guidelines

http://www.overnightprints.com/main.php?A=specs_common

http://www.overnightprints.com/main.php?A=USPS



The product will be cut on the trim mark (blue line)

Place all text and important image(s) inside the safe zone (red line)