If you have a double-sided card, make and upload two files, one for each side.

Before you start, check your Color Settings: for CMYK, select "U.S. Sheetfed Coated v2".

Open the Layers Palette. Place your design on the *Design layer*.

Use the layer safe zone & instructions for reference only and delete it before submitting to Overnight Prints.

Keep all text and important image(s) within the *safe zone* to avoid being cut.

Extend your background all the way to the edge, beyond the trim mark for proper full bleed - if desired by the design.

If you're designing a mailpiece to be mailed through the US Postal Service, make sure it meets all postal regulations

- make layer *postal regulations* visible for guidelines.

To prepare your file for submitting to Overnight Prints:

Delete the layers safe zone & instructions and postal regulations and

leave your **Design layer** and **Art Board layer** only. Do not delete the locked **layer Art Board**; this will ensure your file remains at the full bleed size when uploaded.

Save your file in .PDF, .EPS, .TIF, or .JPG format in CMYK Color mode, with a resolution of 300 DPI.

Note: You may also submit your files in .AI (Illustrator version 8 or earlier), but our file uploader does not accept .AI files saved for versions later than Illustrator 8.

For more information on specs, orientation guide, common mistakes and postal regulations, visit:

http://www.overnightprints.com/main.php?A=specs

http://www.overnightprints.com/main.php?A=orientation

http://www.overnightprints.com/main.php?A=specs\_guidelines

http://www.overnightprints.com/main.php?A=specs\_common

http://www.overnightprints.com/main.php?A=USPS

Extend your background design all the way to the Art Board's edge, on all four sides

The product will be cut on the trim mark (blue line)

Place all text and important image(s) inside the safe zone (red line)

